

DH-DSA3208(-F)

32" Distributed Storage Operation Host



Features:

- Support picture, video, text information releasing real-time, 8ch 1080P video decoding and storage
- Built-in network routing function, LAN/Wi-Fi/3G/4G network access, built-in Wi-Fi hotspot, offer wireless network server
- Support IP camera access from 50 different brands all over the world
- Compatible with Dahua SDK, can easily access into other platform
- Built-in 8 PoE port
- Instant palyback, adjustable from 5min to 1hour
- Widely used in the community, scenic region, supermarket, hotel, metro, train station, airport and other public places

Technical Specification

Specification

Model	DH-DSA3208(-F)	
Panel Size	31.5" TFT-LCD	
Display Ratio	16:9	
Maximum Resolution	1920×1080	
Display Color	16.7M	
Brightness (nits)	400cd/ m ²	
Contrast	1400:1	
Viewing Angle	178°/178°	
Backlight	LED	
Response Time	10ms	
Display Mode	Horizontal, Vertical	

Performance

System	Android5.1	
Network	DH-DSA3208	DH-DSA3208-F
	Wired, Wi-Fi, Wi-Fi hotspot	4G, Wired, Wi-Fi, Wi-Fi hotspot
RAM	Android: 1G	
	NVR: 512M	
Storage Capacity	Android: 16G	
	NVR: max 8T hard disk	



Decoding Ability	Android: 3CH@1080P
	NVR: 6CH@1080P
Access Ability	8CH HD video input, max 160Mbps stream
Picture Split Mode	1, 4, 8, 9
Built in Loudspeaker	1

Interface

Operation Interface	Web, Local GUI, Android app
Video Output	1 HDMI, 1 LVDS
Audio Input	1 RCA
Audio Output	1 RCA
Alarm Input	12CH
Alarm Output	4CH
RS-232	1 RS-232(for debug)
USB	Android: 1 USB3.0, 1 USB2.0
	NVR: 1 USB3.0, 2 USB2.0
Ethernet	1000M wan port, 4×100M lan port
PoE	8 RJ45(10M/100M)
Power Supply	12V1A

Others

Dimension	770.0×470.0×86.0mm
Gross Weight	23.0kg
Installation Mode	Wall-mounted
Power	AC100~240V, 50Hz/60Hz
Standard Consumption	≤160W
Storage Environmet	Temperature: -10C~+55C
	Humidity: 10%~90%
Ingress Protection	IP54