

DHI-ASL8112R-B DHI-ASL8112K-B DHI-ASL8112S-B

Bluetooth smart lock



Features

- 5-way opening: Bluetooth, Fingerprints, Mifare Cards, passwords and mechanical keys
- Voice prompt: All settings can be finished by following voice prompt
- Privacy password: xxx+password+xxx, preventing password to be seen by others
- Passage Mode and Non-disturbance Mode optional
- Auto lock when come across a consecutive invalid passwords or cards
- Low Voltage alarm (<4.5V), doorbell
- Huge storage: 50 Fingerprints, 50 cards, 50 passwords
- Emergency power supply outside
- Three colors optional
- Zinc alloy material

Technical Specification

Card

Card Type	Mifare 1
Card Features	Contactless, high security, all-in-one possible
Sensor Distance	< 20mm
Sensor Time	< 0.5s
Storage Capacity	50

Password

Keyboard Type	All-touch keypad
Password Length	6-12 bits
Storage Capacity	50

Fingerprint

Sensor	Capacitive
False Rejection Rate	≤0.9%
False Accept Rate	≤0.0001%
Fingerprint Capacity	50

Battery

Working Voltage	6V, "AA" battery (4pcs)
Battery Life	About 1 year (10 units/D)
Low Battery Warning	< DC4.5V
Emergency Power Supply	9V battery

Structure

Door Thickness	45-65mm (customizable)
Backset	60mm
Central Distance	68mm
Product Standard	GA701-2007
Material	Zinc alloy

General

Working Temperature	-10°C~+55°C
Relative Humidity	10%~93%
Salt spray test	≥200h
Lock case test	≥100000 times
Package size	410*225*155(mm)
Gross weight	6Kg
Restore Default	Support
Reset	Support
Ring	Support
Built-in Buzzer	Support
Built-in Loudspeaker	Support

DHI-ASL8112R-B DHI-ASL8112K-B DHI-ASL8112S-B

Dimensions

	DHI-ASL8112K-B	Black bronze(K)
	DHI-ASL8112R-B	Antique copper(R)
	DHI-ASL8112S-B	Satin silver(S)

