

DH-SD8A840VI-HNI

4K 40x Starlight IR PTZ Network Camera



- 1/1.8" 8Megapixel STARVIS™ CMOS
- Powerful 40x optical zoom
- Starlight technology
- Max. 25/30fps@4K
- Support Hi-PoE
- Smart wiper
- IR distance up to 450m
- IP67



System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, this camera provides an all-in-one solution for capturing long distance video surveillance for outdoor applications. Together with infrared illumination and Starlight Technology, the camera is the perfect solution for dark, lowlight applications. The series combines a day/night mechanical IR cut filter for the highest image quality in variable lighting conditions during the day, and True WDR for applications with direct sunlight or glare.

Functions

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.002lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

Smart Wiper

With Dahua smart wiper technology, the wiper can be started/stopped automatically when the build-in rain sensor discerns whether it rains. The technology could offer better surveillance performance against wet weather and reduce dependence on manual operation.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -40 °C to +70 °C (-40 °F to +158 °F) with 95% humidity. Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications.

Protection

The camera allows for ±25% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 8KV lightning rating provides effective protection for both the camera and its structure against lightning.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification			
Camera			
Image Sensor	1/1.8” STARVIS™ CMOS		
Effective Pixels	3840(H) x 2160(V), 8 Megapixels		
Scanning System	Progressive		
Electronic Shutter Speed	1/1s~1/30,000s		
Minimum Illumination	Color: 0.002Lux@F1.4; B/W: 0.0002Lux@F1.4; 0Lux@F1.4 (IR on)		
S/N Ratio	More than 56dB		
IR Distance	Distance up to 450m (1476ft)		
IR On/Off Control	Auto/Manual		
IR LEDs	10		
Smart Wiper	Support		
Lens			
Focal Length	5.6mm~223mm		
Max. Aperture	F1.4~ F4.8		
Angle of View	H: 63.9° ~ 2.0°		
Optical Zoom	40x		
Focus Control	Auto/Manual		
Close Focus Distance	100mm~ 1000mm		
DORI Distance			
*Note: The DORI distance is a “general proximity” of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.			
Detect	Observe	Recognize	Identify
4400m(14435ft)	1740m(5708ft)	880m(2887ft)	440m(1443ft)
PTZ			
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -30° ~ 90°,auto flip 180°		
Manual Control Speed	Pan: 0.1° ~240° /s; Tilt: 0.1° ~100° /s		
Preset Speed	Pan: 240° /s; Tilt: 120° /s		
Presets	300		
PTZ Mode	5 Pattern, 8 Tour, Auto Pan ,Auto Scan		
Speed Setup	Human-oriented focal Length/ speed adaptation		
Power up Action	Auto restore to previous PTZ and lens status after power failure		
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period		
Protocol	DH-SD, Pelco-P/D (Auto recognition)		
Intelligence			
Event Trigger	Motion detection, Video tampering , Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly		

Auto Tracking	Support
IVS	Tripwire, Intrusion, Abandoned/Missing
Advanced Intelligent Functions	Face Detection, Heat Map
Video	
Compression	H.265+/H.265/H.264+/H.264
Streaming Capability	3 Streams
Resolution	4K(3840x2160)/1080P(1920×1080)/1.3M(1280x960)/720P(1280×720)/D1(704×576/ 704×480)/CIF(352×288/352×240)
Frame Rate	Main stream: 4K(1~25/30fps), 1080P/1.3MP/720P (1~25/30fps)
	Sub stream1: D1/CIF(1 ~ 25/30fps)
	Sub stream2: 1080P/1.3M/720P (1 ~ 25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 512K ~ 8192Kbps
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR(120dB)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detection	Support
Region of Interest	Support
Electronic Image Stabilization (EIS)	Support
Optical Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Audio	
Compression	G.711a/G.711mu/PCM/G.726/AAC/G722.1/G.729/ MPEG2-Layer2
Network	
Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage),Local PC for instant recording, Micro SD card 256GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android

Certifications

Certifications

CE: EN55032/EN55024/EN50130-4
FCC: Part15 subpartB, ANSI C63.4- 2014
UL: UL60950-1+CAN/CSA C22.2, No.60950-1

Interface

Video Interface 1 port(BNC, 1.0V[p-p], 75Ω)

RS485 1

Audio I/O 1/1

Alarm I/O 7/2

Electrical

Power Supply AC24V/3A(±25%), Hi-PoE

Power Consumption 26W, 38W (IR on, Heater on)

Environmental

Operating Conditions -40°C ~ 70°C (-40°F ~ +158°F) / Less than 95% RH

Ingress Protection IP67

Vandal Resistance N/A

Construction

Casing Metal

Dimensions Ø262(mm) x 415.6 (mm)

Net Weight 8.5kg(18.74lb)

Gross Weight 14.3kg(31.53lb)

Ordering Information

Type	Part Number	Description
4K PTZ Camera	DH-SD8A840VI-HNI	4K 40x Starlight IR PTZ Network Camera, WDR, PAL
	DH-SD8A840VIN-HNI	4K 40x Starlight IR PTZ Network Camera, WDR, NTSC
	SD8A840VI-HNI	4K 40x Starlight IR PTZ Network Camera, WDR, PAL
	SD8A840VIN-HNI	4K 40x Starlight IR PTZ Network Camera, WDR, NTSC
Accessories	PFB306W	Wall Mount
	AC24V/3A	Power Adapter
	PFA120	Junction Box
	PFA140	Power Box
	PFA150	Pole Mount
	PFA151	Corner Mount

Accessories

Included:



PFB306W
Wall Mount



AC24V/3A
Power Adapter

Optional:




PFA120
Junction Box



PFA140
Power Box



PFA150
Pole Mount



PFA151
Corner Mount

Junction Mount	Power Box Mount
PFB306W + PFA120	PFB306W + PFA140
Corner Mount	Pole Mount
PFB306W + PFA151	PFB306W + PFA150

Dimensions (mm)

