

# ASI1212F/ASI1212F-D

## Access Standalone



- PC+ABS housing material, and glass material for front panel , applicable for indoor scenario
- 2.8 inch LCD touch screen display with resolution of 240x320
- Deep learning algorithm makes fingerprint recognition time 1.5 s
- Support card, fingerprint, password
- Support 30,000 users, 30,000 cards, 3,000 fingerprints, 150,000 records
- Support OSDP, TCP/IP



### Technical Specification

Models	ASI1212F	ASI1212F-D
--------	----------	------------

#### System

Main Processor	Embedded processor
Network Protocol	IPv4, TCP, P2P
Button Type	Touch button
OSDP Protocol	Yes (only supported as a host)

#### Basic

Display	2.8 inch TFT touch screen
Screen Type	Capacitive screen
Resolution	240(H)x320(V)
Voice Prompt	Yes
Buzzer	Yes
Housing Material	PC+ABS

#### Function

Unlock Mode	Card/remote/password/fingerprint	
Card Type	IC card	ID card
Period List	128	
Holiday Period	128	
Network Update	Yes	
First Card Unlock	Yes	

Remote Verification	Yes
Blacklist/Whitelist	Yes
Ads Broadcast	Support graphic advertisement play
Peripheral Card Reader	1 RS-485, 1 Wiegand
Group Combination	Card/remote/password/fingerprint
Web Configuration on PC	Yes
Web Configuration on Mobile	Yes

#### Performance

Card Reading Distance	1 cm–3 cm (0.03 ft–0.10 ft)
Fingerprint Sensor Type	Optical fingerprint
Fingerprint Verification Mode	1:N, 1:1
Fingerprint Comparison Time	1.5 s

#### Capacity

User	30,000
Fingerprint	3,000
Card	30,000
Password	30,000
Record	150,000

#### Port

RS-485	1
Wiegand	1 (input or output)

USB	1 USB2.0 port
Network	One 10/100 Mbps self-adaptive network port
Alarm Input	1
Alarm Output	1
Alarm Linkage	Yes
Unlock Button	1
Door Status Detection	1
Lock Control	1


## Alarm

Anti-passback	Yes
Tamper	Yes
Duress	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
Duress Fingerprint	Yes


## General

Power Supply	DC 12V 1A
Power Consumption	≤ 4.0W (standby), ≤ 6.0W (working)
Dimensions (H×W×D)	114.5 mm × 114.5 mm × 32.5 mm (4.51" × 4.51" × 1.28")
Packing Dimensions (H×W×D)	Packing box: 187 mm × 164 mm × 72 mm (7.36" × 6.46" × 2.83") Protective box: 585 mm × 390 mm × 360 mm (23.03" × 15.35" × 14.17")
Operating Temperature	-10°C to +45°C (14°F to 113°F)
Operating Humidity	5%RH-90%RH (no condensation)
Operating Environment	Indoor
Gross Weight	415.0 g (0.91 lb)
Installation	Surface mount, flush mount, 86 case mount
Certifications	CE, FCC

## Dimensions (mm[inch])



## Application



## Ordering Information

Type	Model	Description
Access Standalone	ASI1212F	Access standalone(IC card)
Access Standalone	ASI1212F-D	Access standalone(ID card)