

# DH-IPC-HDBW5842E-Z4E-S2

## 8 MP IR Vari-focal Dome WizMind Network Camera



Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

### Series Overview

With starlight solution and deep learning algorithm, Dahua WizMind 5 Series network camera has various intelligent functions, including face capture, perimeter protection and people counting, which greatly improve the accuracy of video analysis. The series camera supports dust-proof function, waterproof function and vandal-proof function, complying with the standards of IP67 and IK10 (Supported by some select models).

### Functions

#### Face Detection

Dahua Face Detection technology can detect the face in the image. With deep learning algorithm, the technology supports detecting, tracking, capturing and selecting the best face image, and then outputs face snapshot.

#### Face Attributes

With deep learning algorithm, the network camera can recognize face attributes, such as gender, age, expression, glasses, mouth mask, and beard.

#### Perimeter Protection

With deep learning algorithm, Dahua Perimeter Protection technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

- 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.
- Outputs max. 8MP (3840× 2160) @30 fps.
- Max. IR distance: 80 m.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card
- 24V AC/PoE/12V DC power supply.
- ePoE, IP67, IK10 protection.
- SMD 3.0.



### People Counting

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/daily reports to meet your requirements.

### ePoE

Dahua's innovative ePoE technology offers a new solution to transmit power and data over long distances between cameras and network switch, allowing more flexible design of surveillance system, improving reliability, reducing installation time and saving money. ePoE technology encompasses pure network systems where a single CAT6 cable can carry signals up to 300 m (984 ft) at 100 Mbps, 800 m (2625 ft) at 10 Mbps.

### Cyber Security

Dahua network cameras employ a series of security technologies, including security authentication and authorization, access control protocols, trusted protection, encrypted transmission and encrypted storage. These technologies improve the camera's defense against external cyber threats and prevent malicious programs from compromising the device.

### Protection (IP67, IK10, wide voltage)

**IP67:** The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normal after soaking in 1 m deep water for 30 minutes.

**IK10:** The enclosure can stand the punch more than 5 times from a 5 kg hammer falling from a height of 40 cm (Impact energy is 20J).

**Wide voltage:** The camera allows  $\pm 30\%$  (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

**Technical Specification**

**Camera**

Image Sensor	1/1.8"CMOS
Max. Resolution	3840 (H) × 2160 (V)
ROM	128 MB
RAM	1 GB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.004 lux@F1.4 (Color, 30 IRE) 0.0004 lux@F1.4 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>56 dB
Illumination Distance	80 m (262.5 ft)
Illuminator On/Off Control	Auto; manual; zoomprio
Illuminator Number	3 (IR)
Pan/Tilt/Rotation Range	Pan: 0°–355° Tilt: 0°–80° Rotation: 0°–355°

**Lens**

Lens Type	Motorized vari-focal				
Mount Type	Module				
Focal Length	8 mm–32 mm				
Max. Aperture	F1.4 (Constant)				
Field of View	Horizontal: 42°–14.9° Vertical: 23.3°–8.6° Diagonal: 48.5°–16.9°				
Iris Control	Auto				
Close Focus Distance	W: 3.0 m (9.84 ft) T: 5.5 m (18.04 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	213.6 m (700.8 ft)	85.4 m (280.2 ft)	42.7 m (140.1 ft)	21.4 m (70.2 ft)
	T	572.8 m (1879.3 ft)	229.1 m (751.6 ft)	114.6 m (376.0 ft)	70.2 m (188.0 ft)

**Smart Event**

IVS	Abandoned object; moving object
Heat Map	Yes

**Professional, intelligent**

IVS (Perimeter Protection)	Tripwire; intrusion; fast moving (the three functions support the classification and accurate detection of vehicle and human); loitering detection; people gathering; parking detection
Face Detection	Face detection; track; snapshot optimization; snapshot; face enhancement; face exposure; face matting setting; face, single inch photo; three snapshot methods: real-time snapshot, optimized snapshot, quality priority snapshot; face angle filter; optimization time setting

**People Counting**

Support the counting of enter number, leave number and pass number, and displaying and outputting yearly/monthly/daily reports.  
Support the counting of number in area, and 4 rules configuration. Count number of people or stay time and link alarm.  
Support queue management, and 4 rules configuration. Count number of people or stay time and link alarm.

**Intelligent Search**

Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos.

**Video**

**Video Compression**

H.265; H.264; H.264H; H.264B; MJPEG (Only supported by the sub stream)

**Smart Codec**

Smart H.265+/H.264+

**Video Frame Rate**

Main stream: 3840× 2160 (1 fps–25/30 fps)  
Sub stream: D1 (1 fps–25/30 fps)  
Third stream: 1080p (1 fps–25/30 fps)  
\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

**Stream Capability**

3 streams

**Resolution**

3840 × 2160; 3072 × 2048; 3072 × 1728; 2592 × 1944; 2688 × 1520; 2048 × 1536; 2304 × 1296; 1080p (1920 × 1080); 1.3 MB (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)

**Bit Rate Control**

CBR/VBR

**Video Bit Rate**

H.264: 3 kbps-20480 kbps  
H.265: 3 kbps-20480 kbps

**Day/Night**

Auto (ICR)/Color/B/W

**BLC**

Yes

**HLC**

Yes

**WDR**

120 dB

**White Balance**

Auto; natural; street lamp; outdoor; manual; regional custom

**Gain Control**

Auto; manual

**Noise Reduction**

3D NR

**Motion Detection**

OFF/ON (4 areas, rectangular)

**Region of Interest (RoI)**

Yes (4 areas)

**Image Stabilization**

Electronic Image Stabilization (EIS)

**Defog**

Yes

**Image Rotation**

0°/90°/180°/270° (Support 90°/270° with 4 M resolution and lower)

**Mirror**

Yes

**Privacy Masking**

8 areas

**Audio**

**Audio Compression**

PCM; G.711a; G.711Mu; G.726; G.723

**Alarm**

**Alarm Event**

No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; defocus detection; scene changing; intrusion; tripwire; abandoned object; missing object; fast moving; parking detection; loitering detection; people gathering; input abnormal detection; intensity change detection; people counting; face detection; people counting in area; stay alarm; people No. exception detection; queue management

### Network

Network Port	RJ-45 (10/100 Base-T)
SDK and API	Yes
Cyber Security	Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTPS; trusted boot; trusted execution; trusted upgrade
Network Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; P2P
User/Host	20 (Total bandwidth: 80 M)
Storage	FTP; SFTP; Micro SD card (Support max. 256 G); NAS
Browser	IE: IE8 and later Chrome Firefox
Management Software	Smart PSS; DSS; DMSS
Mobile Client	iOS; Android

### Certification

Certifications	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
----------------	--

### Port

Audio Input	1 channel (terminal)
Audio Output	1 channel (terminal)
Alarm Input	1 channels in: 5 mA 5 VDC
Alarm Output	1 channels out: 300 mA 12 VDC
Alarm Output	2 channels out: 1,000 mA 30 VDC/500 mA 50 VDC

### Power

Power Supply	12 VDC (±25%)/24 VAC (±30%)/PoE (802.3af)/ePoE
Power Consumption	Basic power consumption: 5.1 W (12V DC); 5.0 W (24 VAC); 5.7 W (PoE) Max. power consumption (H.265 + max. stream + intelligent function + IR LED + focus): 12.8 W (12 VDC); 12.3 W (24 VAC); 12.5 W (PoE)

### Environment

Operating Temperature	-30 °C to +60 °C (-22 °F to +140 °F)/Less than 95% RH
Storage Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Protection	IP67, IK10

### Structure

Casing	Metal, plastic
Product Dimensions	Φ159.1 mm × 118.1 mm (6.26" × 4.65")
Net Weight	0.95 kg (2.09 lb)
Gross Weight	1.20 kg (2.65 lb)

### Ordering Information

Type	Model	Description
8MP Camera	DH-IPC-HDBW5842EP-ZE-0832-DC12AC24V-S2	8 MP IR Vari-focal Dome WizMind Network Camera, PAL
	IPC-HDBW5842EP-ZE-0832-DC12AC24V-S2	8 MP IR Vari-focal Dome WizMind Network Camera, PAL
Accessories (Optional)	PFA138	Junction Box Bracket
	PFB210W	Wall Mount Bracket
	PFB300C	Ceiling Mount Bracket
	PFA152-E	Pole Mount Bracket
	PFB201C	In-ceiling Mount Bracket
	PFA101	Mount Adapter
	PFM321D	12 VDC 1A Power Adapter
	LR1002-1ET/1EC	Single-port Long Reach Ethernet over Coax Extender
PFM900-E	Integrated Mount Tester	

### Accessories

#### Optional:



PFA138  
Junction Box  
Bracket



PFB210W  
Wall Mount  
Bracket



PFB300C  
Ceiling Mount  
Bracket



PFA152-E  
Pole Mount  
Bracket



PFB201C  
In-ceiling Mount  
Bracket



PFA101  
Mount Adapter




PFM321D  
12 VDC 1A Power  
Adapter



LR1002-1ET/1EC  
Single-port Long Reach  
Ethernet over Coax  
Extender



PFM900-E  
Integrated Mount  
Tester



**Dimensions (mm[inch])**

