

DH-PFM920I-5EU-C/U

305m UTP CAT5E Cable



Features

- 305m UTP CAT5E;
- Support PoE long-distance transmission;
- Excellent OFC with 99.99% OFC(oxygen free copper) purity;
- Environmentally-friendly outer sheath, meet the CPR E/ UL CM class;
- Top-notch quality guarantee for 10 years.

Technical Specifications

Model		DH-PFM920I-5EU-C	DH-PFM920I-5EU-U
Structure			
Conductor	Material	OFC(oxygen free copper)	
	Structure	4P*0.5±0.01mm	
Insulation	Material	HDPE	
	Min. average thickness	0.195mm	
	Diameter	0.9mm±0.05mm	
	Color(4 Pairs)	Orange, white/orange; green, white/green; blue, white/blue; brown, white/brown	
Rip cord		Yes	
Jacket	Material	PVC, meet the requirement of CPR E class	PVC, meet the requirement of UL CM class
	Min. average thickness	0.40mm	
	Diameter	5.0±0.50mm	
	surface	Smooth, full and tight	
	Color	Orange and white are optional	
General	Length	305m(1000.66ft)	
	N.W.	8.75kg(19.29lb)	
	Packaging dimension	360mmx360mmx210mm(14.17"x14.17"x8.27")	
	Weight (with packaging)	10.0(22.05lb)	
Mechanical properties			
Insulation	Tensile strength	≥16MPa	
	Elongation at break	≥300%	
	Peeling property	No damage to insulation or conductor	
Jacket	Tensile strength	Before aging: ≥13.5MPa After aging: ≥12.5MPa	Before aging: ≥13.5MPa Retention rate of tensile strength after aging: ≥85%
	Elongation at break	Before aging: ≥150% After aging: ≥125%	Before aging: ≥150% Retention rate of elongation at break after aging: ≥50%
	Aging condition	100°C*24h*7d	
	Peeling property	No damage to insulation, cold bending (-20C *4h), the outer diameter of the cable is 8 times, without cracking.	No damage to insulation, cold bending (-15C *4h), the outer diameter of the cable is 8 times, without cracking.
Electrical performance (20°C)			
Characteristic impedance (1-250MHz)		100±15Ω	
DC resistance		≤9.5Ω/100m	
Max. unbalance rate of line pairs' direct current		≤5%	
Time delay		≤45ns/100m	



Cable Series | DH-PFM920I-5EU-C/U

Max. mutual capacitance	5.6nF/100m
Min. insulation resistance	5000MΩ·km

Order Information

Type	Part Number	Description
Cable Series	DH-PFM920I-5EUN	305m UTP CAT5E cable _Dahua brand; CPR E class; Distribution
	DH-PFM920I-5EU-C	305m standard UTP CAT5E cable _Dahua brand; CPR E class
	DH-PFM920I-5EU-U	305m standard UTP CAT5E cable _Dahua brand; UL CM class
	DH-PFM920I-6UN-C	305m UTP CAT6 cable _Dahua brand; CPR E class; Distribution
	DH-PFM920I-6UN-U	305m UTP CAT6 cable _Dahua brand; UL CM class; Distribution

Dimensions (mm/inch)



Package Information

- 305m UTP CAT5E cable *1