

# DHI-NVR4104/4108HS-P-4KS2

4/8 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder



- Smart H.265+/H.265/Smart H.264+/H.264
- · Max 80Mbps Incoming Bandwidth
- Up to 8MP Resolution for Preview and Playback
- · Up to 2ch@4K/8ch@1080P decoding
- HDMI/VGA simultaneous video output
- Support IPC UPnP, 4PoE ports













#### **System Overview**

Dahua NVR4000-4KS2 is introduced as the first Lite series NVR that supports for 4K and H.265 encoding technology with excellent performance at an affordable price. For applications where image details are highly required, it delivers the capability of 4K resolution processing. The NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

Due to its cost-effective and easy-to-install design, this NVR is ideal for a wide range of applications such as public safety, water conservancy, transportation, city centers, education, and financial institutions.

The NVR is compatible with numerous third-party devices making it the perfect solution for surveillance systems that work independently of video management system (VMS). It features an open architecture that supports for multi-user access and is compatible with ONVIF 2.4 protocol, enabling interoperability with IP cameras.

#### **Functions**

4K Resolution

4K resolution is a revolutionary breakthrough in image processing technology. 4K delivers four times the resolution of standard HDTV 1080p cameras and offers superior picture quality and image details. 4K resolution improves the clarity of a magnified scene to view or record crisp forensic video from large areas.

#### Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

#### Intelligent Video System

Working with IVS-enabled IP cameras, the NVR recognizes and records video that contains IVS data on all IP channels. The NVR records standard intelligence at-the-edge features, as well as premium IVS features that detect abandoned or missing objects, Tripwire violations, and intrusion violations. The NVR is also capable of recording business analysis data — Facial Detection, People Counting, and Heat Map — from IP cameras with built-in Intelligent Business Analytics.

ANR (Automatic Network Replenishment Technology)

Network Video Recorders with the ANR function automatically store video data on an IP camera SD card when the network is disconnected. After recovery of the network, the NVR automatically retrieves the video data stored on the camera.

#### DMSS

The DMSS app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access NVR devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere!



Backup Mode


USB Device/Network

Technical Specification		Third-party Support		
System  Main Processor	Quad-core embedded processor	Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, PSIA, Samsung, Sanyo, Sony, Watchnet and more	
Operating System	Embedded LINUX	Network		
Aduio and Video		Interface	1 RJ-45 Port (10/100Mbps)	
IP Camera Input	4/8 Channel	Ethernet Port	1 Independent 100Mbps Ethernet Port	
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	PoE	4 Ports(IEEE802.3at/af)	
Display			HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP,	
Interface	1 HDMI, 1 VGA	Network Function	SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, SNMP, IP Search (Support Dahua IP camera, DVR, NVS, etc.), Easy4ip	
Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720	Max. User Access	128 users	
	VGA: 1920×1080, 1280×1024, 1280×720	Smart Phone	iPhone, iPad, Android	
Decoding Capacity	2ch@4K(30fps)/8ch@1080P(30fps)	Interoperability	ONVIF 2.4, SDK, CGI	
Multi-screen Display	4CH: 1/4	Storage		
Width-screen display	8CH: 1/4/8/9	Internal HDD	1 SATA III Port, Up to 6 TB capacity for each HDD	
OSD	Camera title, Time, Camera lock, Motion detection, Recording	HDD Mode	Single	
Recording		Auxiliary Interface	Auxiliary Interface	
Compression	Smart H.265+/H.265/Smart H.264+/H.264	USB	2 ports (1 Rear USB2.0, 1 Front USB2.0)	
Resolution	$8 \mathrm{Mp/6Mp/5MP/4MP/3MP/1080P/1.3MP/720P}$ etc.	RS232	N/A	
Record Rate	80Mbps	RS485	N/A	
Bit Rate	16Kbps ~ 20Mbps Per Channel	Electrical		
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop	Power Supply	DC48V/1.5A	
Record Interval	1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec	Power Consumption	NVR: <7.5W (Without HDD)  PoE: Max 25.5W for single port, 50W in total	
Video Detection and Alarm		Environmental	. OZI mak Zolow lov single por glow in cotal	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, Snapshot, Buzzer and Screen Tips	Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa	
Video Detection	Motion Detection, MD Zones: 396 (22 × 18),	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH	
	Video Loss and Tampering	Construction		
Alarm input	N/A	Dimensions	Compact 1U, 260mm×224.9mm×47.6mm (10.2" x 8.9" x 1.9")	
Alarm output	N/A	Net Weight	0.8kg (1.76 lb) (without HDD)	
Playback and Backup		Gross Weight	1.6kg(3.53 lb)(without HDD)	
Playback	4CH: 1/4 8CH: 1/4/9	Certifications		
6 1 1 1 1	8CH: 1/4/9 Time /Date, MD and Exact Search	CE	EN55032, EN55024, EN50130-4, EN60950-1	
Search Mode	(accurate to second), Smart search	FCC	Part 15 Subpart B, ANSI C63.4-2014	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Backup Selection, Digital Zoom	UL	UL60950-1	

# Lite Series | HI-NVR4104/4108HS-P-4KS2

Ordering Information			
Туре	Part Number	Description	
4 Channel NVR	DHI-NVR4104HS-P-4KS2	4 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder	
8 Channel NVR	DHI-NVR4108HS-P-4KS2	8 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder	

## **Rear Panel**



## Dimensions (mm)

