

LM18-L100

18.5" Monitor



Features:

- Industrial level LCD panel, suitable for continuous 24/7 operation
- High fidelity digital processing for a brilliant and vivid video
- 5ms fast response time for no motion blur, judder or ghosting
- Good compatibility with CVBS camera
- Built in speakers



Technical Specification

Model

| | |
|-------|-----------|
| Model | LM18-L100 |
|-------|-----------|

Display

| | |
|----------------------|----------------------|
| Screen Size | 18.5" |
| Aspect Ratio | 16:9 |
| Resolution | 1366×768 |
| Backlight | LED |
| Brightness/Luminance | 200cd/m ² |
| Contrast Ratio | 600:1 |
| Display Color | 16.7M(8bit) |
| Viewing Angle(H/V) | 178°(H)/178°(V) |
| Response time | 5ms |
| Refresh Rate | 60Hz |

Signals

| | | |
|--------|--------------------------------------|------|
| Input | VGA(D-Sub)×1, HDMI×1, BNC×1, Audio×1 | |
| Output | Speaker | 3W×2 |

General

| | |
|--------------|-------------------------------|
| Power Supply | AC100~240V (+/-10%), 50/60 Hz |
|--------------|-------------------------------|

| | | |
|--------------------------------|---------------------------------------|------------------------|
| Consumption (Standard) | ≤30W | |
| Consumption (Standby) | ≤0.5W | |
| Type | Internal | |
| Net Weight | 2.8kg (6.2lb) | |
| Gross Weight | 4.3kg (9.5lb) | |
| Bezel Width | 17mm (U), 14.5mm (L/R), 26mm (B) | |
| VESA | 75×75mm (3.0"×3.0") | |
| Dimension without base (W×H×D) | 442.0×276.0×51.5mm (17.4"×10.9"×2.0") | |
| Work Environment | Temperature | 0°C~ 40°C (32°F~104°F) |
| | Humidity | 10%~85% |

Accessory

| | |
|----------|----------------------------------|
| Standard | VGA cable, power cable, pedestal |
| Optional | Hanging bracket |

Certifications

| | |
|----------------|--------|
| Certifications | CE/FCC |
|----------------|--------|

Dimensions(mm)

