

DH-IPC-HDBW7442H-Z4

4MP AI IR Dome Network Camera



System Overview

With advanced deep learning algorithm, Dahua Ultra AI series network camera supports various intelligent functions and satisfies the requirements in different scenes. The camera can accurately detect person, vehicle, and non-motor vehicle, face, ANPR, and liveness. This series camera has ultra starlight night version effect, and works with ultra-low stream. It supports dust-proof function, waterproof function and vandal-proof function, complying to the standards of IP67 and IK10.

Functions

Face Detection

Dahua Face Detection technology can detect the face in the image. With deep learning algorithm, the technology supports detecting, tracking, capturing and selecting the best face image, and then outputs face snapshot.

People Counting

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.

Video Metadata

With deep learning algorithm, Dahua Video Metadata technology can detect, track, capture vehicle, non-motor vehicle and people, and select the best images, and extract attributes.

Smart Codec

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

ePoE

Dahua ePoE technology provides a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

- 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition
- Max outputs 4MP (2688×1520) @50 fps/60 fps
- H.264&H.265 coding, high compression ration · Wide dynamic, day/night, 3D noise reduction, AWB, HLC, BLC
- ROI, SVC, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- With deep learning algorithm, it supports people counting, face recognition, perimeter protection etc.
- 24V AC/PoE/12V DC power support
- Five streams for three-channel HD video
- IP67, IK10 protection grade



Perimeter Protection

With deep learning algorithm, Dahua Perimeter Protection technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

Privacy Protection

Dahua Privacy Protection technology can mask the detected face and human body to protect the privacy of some special targets.

Technical Specification					
Camera					
Image Sensor		1/1.8" 4Megapixel progressive CMOS			
Effective Pixels		2688 (H) × 1520 (V)			
ROM		4 GB			
RAM		2 GB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual 1/3 s–1/100000 s			
Min. Illumination		0.001 Lux@F1.6			
IR Distance		Distance up to 80 m (262.5 ft)			
IR On/Off Control		Auto			
IR LEDs Number		3 (IR LEDs)			
Pan/Tilt/Rotation Range		Pan: 0°–355° Tilt: 0°–80° Rotation: 0°–355°			
Lens					
Lens Type		Motorized vari-focal			
Mount Type		Module interface			
Focal Length		8 mm–32 mm			
Max. Aperture		F1.6			
Field of View		Horizontal: 40° (W)–15° (T) Vertical: 23° (W)–9° (T) Diagonal: 46° (W)–18° (T)			
Iris Type		Auto aperture			
Close Focus Distance		W: 2.5 m (W: 8.20 ft) T: 6 m (T: 19.68 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	151 m (495.4 ft)	60.7 m (199.1 ft)	30.3 m (99.4 ft)	15.1 m (49.5 ft)
	T	400 m (1312.3 ft)	160 m (524.9 ft)	80 m (262.5 ft)	40 m (131.2 ft)
Smart event					
General IVS Analytics		Abandoned object, moving object			
Professional, intelligent					
Perimeter Protection		Tripwire, intrusion, fast moving (the three functions support the classification and accurate detection of vehicle and human); parking detection, loitering detection, and people gathering.			
Face Detection		Face detection, track, priority, snapshot, face enhancement, face exposure, face attribute extract, 6 attributes and 8 expressions: Gender, age, glasses, expressions (anger, sadness, disgust, fear, surprise, calm, happiness and confusion), mask, beard Face matting setting: face, single inch photo Three snapshot methods: real-time snapshot, priority snapshot, quality priority Face angle filter Priority time setting			
ANPR		ANPR, track, priority, snapshot Vehicle attributes: license plate, vehicle type, vehicle color, vehicle brand Other attributes: sun visor, seat belt, smoking, phoning, in-car accessories, annual vehicle inspection mark			

Video Metadata		Support human body, human face, motor vehicle and non-motor vehicle image capture and attributes extraction.
People Counting		People counting (count the entry number, exit number and pass number), display and output daily/monthly/annual statistics, No. in area
Intelligent Search		Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos.
Video		
Video Compression		H.265, H.264, H.264H, H.264B, MJPEG
Smart Codec		Yes
Video Frame Rate		Main Stream: 2688 × 1520 (1–50/60 fps) sub stream 1: 704 × 576 (1–25/30 fps) sub stream 2: 1920 × 1080 (1–25/30 fps) sub stream 3: 1920 × 1080 (1–25/30 fps) sub stream 4: 704 × 576 (1–25/30 fps)
Stream Capability		5 streams
Resolution		4M (2688 × 1520), 3M (2304 × 1296), 1080p (1920 × 1080), 1.3M (1280 × 960), 720p (1280 × 720), D1 (704 × 576/704 × 480), VGA (640 × 480), CIF (352 × 288/352 × 240)
Bit Rate Control		CBR/VBR
Video Bit Rate		H.264: 32 Kbps–10240 Kbps H.265: 12 Kbps–10240 Kbps
Day/Night		ICR switch
BLC		Yes
WDR		140 dB
White Balance		Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control		Auto/Manual
Noise Reduction		3D DNR
Motion Detection		OFF/ON (4 areas, rectangular)
Region of Interest(Rol)		Yes (4 areas)
Electronic Image Stabilization(EIS)		Yes
Smart IR		Yes
Defog		Yes
Image Rotation		0°/90°/180°/270° (Supports 90°/270° with 1080p resolution or below.)
Mirror		Yes
Privacy Masking		4 areas
Audio		
Audio Compression		G.711a; G.711Mu; G726; AAC; G.723
Network		
Network		RJ-45 (10/100/1000 Base-T)
Protocol		HTTP; Htpps; 8021.x; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP; QoS; UPnP; NTP; SFTP; RTMP; Genetec;Bonjour
Interoperability		ONVIF (Profile S/Profile G/Profile T); CGI; P2P

Scene Self-adaptation	Yes
User/Host	20
Edge Storage	FTP; Micro SD card (256 G); NAS; SFTP
Browser	IE: Versions later than IE9 Chrome: Versions later than Chrome 42, Firefox: Versions later than Firefox 48.0.2,
Management Software	Smart PSS, DSS PRO, NVR, IVSS, DMSS
Mobile Phone	IOS, Android

Certification

Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
----------------	--

Port

RS-485	1 (Bit rate: 1200 bps–115200 bps)
Audio Input	Audio Interface: 1/1 channel In/Out
Audio Output	
Alarm Input	3 channel In: 5mA 5V DC
Alarm Output	2 channel Out: 1000mA 30V DC/500mA 50V AC

Power

Power Supply	12V DC/24V AC/POE
Power Consumption	Basic power consumption: 5.4W (12V DC); 5W (24V AC active power); 4.9W (POE); Max power consumption (ICR switch, and IR full intensity): 16.7W (12V DC); 15.7W (24V AC active power); 15.6W (POE);

Environment

Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Storage Temperature	≤95%
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Ingress Protection	IP67, IK10

Structure

Dimensions	129.1 mm × Φ157.9 mm (5.08" × Φ6.22") (L × W × H)
Net Weight	1500g(3.31lb)
Gross Weight	1600 g (3.53 lb)
Installation	Ceiling Mount; side Mount; pole Mount

Ordering Information

Type	Part Number	Description
4MP Camera	DH-IPC-HDBW7442HP-Z4	4MP AI IR Dome Network Camera
	DH-IPC-HDBW7442HN-Z4	4MP AI IR Dome Network Camera
	IPC-HDBW7442HP-Z4	4MP AI IR Dome Network Camera
	IPC-HDBW7442HN-Z4	4MP AI IR Dome Network Camera
Accessories	PFA773	Wall Mount
	PFB210W	Wall Mount
	PFA152-E	Pole Mount
	PFA101	Wall Mount
	PFB300C	Ceiling Mount

Accessories

Optional:



PFA773



PFB210W



PFA152-E



PFA101



PFB300C

Ceiling Mount	Wall Mount	Wall Mount
	PFA773	PFB210W
Wall Mount	Pole Mount	Hang Mount
PFB210W	PFB210W+PFA152-E	PFB300C+PFA101

Dimensions (mm[inch])

