

Dahua Temperature Monitoring Access Control

Facial Recognition/Temperature Monitoring/Integration





Contactless Non-contact detection and measurement 0.3m - 0.8m



High Accuracy Temperature monitoring accurate to ±0.3°C



Fast Response Facial recognition 0.2s Temperature monitoring 0.2s



Easy Installation Rapid installation and flexible deployment



Excellent Compatibility Integration with third party products

Key Features



- Facial recognition is fully integrated with body temperature monitoring. This means no additional staff are required.
- The solution is contactless.
- Extensive storage of facial images and temperature information enabling easy historical access.
- Fast facial recognition and temperature monitoring.
- Integration with third party products such as turnstiles and VMS.

Example Applications



Education





Installation Scenarios



Solutions

Wall Mounted: DHI-ASI7223X-A-T1 Standing Mount: DHI-ASI7223X-A-T1 + DHI-ASF172X-T1 (Bracket)

Terminal + DSS-Express

- \cdot Temperature Accuracy: ±0.3°C
- Temperature Monitoring Distance: 0.3m~0.8m
- Sound Prompt: Abnormal
- temperature alarm



* Design and specifications are subject to change without notice.

DAHUA UK & IRELAND

Quantum House, 60 Norden Road, Maidenhead, Berkshire SL6 4AY Tel: +44 (0) 1628 613 500 sales.UK@dahuatech.com support.UK@dahuatech.com



Ver. 1, May 2020

