


DH-IPC-EBW81242

12MP Panoramic Network IR Fisheye Camera



- 12MP, 1/1.7" CMOS image sensor
- Max output 12MP (4000×3000)@30fps
- 3D DNR, AWB, HLC, BLC, ROI, SVC, SMART H.264/H.265
- People counting in multiple areas, queuing management in multiple areas, heat map (number of people /time), and track map
- 2/2 Alarm in/out, 1/1 audio in/out
- 12V DC/POE power support
- IP67, IK10 protection



System Overview

With advanced chip and deep learning algorithm, AI Fisheye network camera supports many intelligent functions, including people counting in multiple areas, multiple queues management, heat map of number of people and average strand time.

Functions

People Counting

The camera detects and tracks target by using advanced image processing technology and deep learning algorithm. You can draw 4 polygon areas, and count people in each area; When the number of the people in the area is greater than or equal to/lower than or equal to the defined threshold, the alarm will be triggered.

Queue Management

The camera detects and tracks target by using advanced image processing technology and deep learning algorithm. You can draw 4 polygon areas, and count people in each area; When the number of the people in the area or the strand time is greater than or equal to/lower than or equal to the defined threshold, the alarm will be triggered.

Heat Map

It supports heat map of number of people and average strand time. You can observe customer's regions of interest from two aspects: number of people and time.

Panoramic

Panoramic cameras provide 180°, 360° full range of video scene, bringing people a new sense of real life and interactive experience. Dahua provides two kinds of panoramic camera, single lens fisheye camera and multi-lens camera, both of them can offer 180-degree and 360 degree panoramic image. Through working with ptz camera which offer whole scene and region details at same time. It provided new surveillance experience to end user and improved the surveillance quality.

Technical Specification

Camera

| | |
|--------------------------|---|
| Image Sensor | 1/1.7" CMOS |
| Effective Pixels | 4000 (H) × 3000 (V) |
| ROM | 4 GB |
| RAM | 4 GB |
| IR LEDs | 3 (IR LEDs) |
| Electronic Shutter Speed | 1/3 s-1/100000 s (Auto/Manual) |
| Min. Illumination | 0.001 Lux/F2.0 (Colour, 1/3 s, 30 IRE) 0.01 Lux/F2.0 (Colour,, 1/30 s, 30 IRE) 0 Lux/F2.0 (IR on) |
| IR Distance | 10 m (32.8 ft) |
| Scan | Progressive |
| Noise Reduction | 3D DNR |
| WDR | Support |
| S/N Ratio | 50dB |
| Gain control | Manual |
| White Balance | Auto/Natural/street lamp/outdoor/manual/regional Custom |

Lens

| | | | | |
|---------------|----------------------------------|---------------------|--------------------|--------------------|
| Focal Length | 1.85 mm | | | |
| Mount Type | M12 | | | |
| Max. Aperture | F2.0 | | | |
| Aperture Type | Fixed aperture | | | |
| Lens Type | Fixed focal | | | |
| Field of View | Horizontal: 185°; Vertical: 180° | | | |
| DORI Distance | Detect | Observe | Recognize | Identify |
| | 40.0 m (131.3 ft) | 16.0 m (52.6 ft) | 8.0 m (26.3 ft) | 4.0 m (13.1 ft) |

Audio

| | |
|----------------|-------------------------------------|
| Audio Input | 1 channel (RCA port),1 build in MIC |
| Audio Output | 1 channel (RCA port) |
| Audio Encoding | G.711A, G.711Mu, G726, AAC |

Video

| | |
|------------------|--|
| Video Encoding | H.265, H.264, H.264H, H.264B, MJPEG |
| Video Bit Rate | H264: 88Kbps-16384Kbps ;H265: 52Kbps-16384Kbps |
| Video Frame Rate | 50Hz Main Stream (4000 × 3000@25fps), sub Stream (704 × 576@25fps), third Stream (704 × 576@25fps) 60Hz Stream (4000 × 3000@30fps), sub Stream (704 × 480@30fps), third Stream (704 × 480@30fps) Fisheye: 1O (4000 × 3000) 1P (4096 × 1024) 2P (2432 × 2432) 1R (1216 × 1216) 2R (2432 × 2432) 4R (2432 × 2432) 1O + 3R (2432 × 2432) |

| | |
|--------------------|---|
| Resolution | 4000 × 3000, 2880 × 2880, 2880 × 2160, 2048 × 1536 (3M), 1280 × 960 (1.3M), (704 × 576/704 × 480) D1, (352 × 288/352 × 240) CIF |
| Bit Rate Control | CBR/VBR |
| Region of Interest | Yes (4 areas) |
| Smart IR | Yes (Adjust by user) |
| Language | English, Italian, Spanish, Russian, French, German, Portuguese, Polish, Korean, Persian, Czech, Dutch, Arabic, European Spanish |

Alarm

| | |
|--------------|---|
| Alarm Input | 2 channels (Wet contact, and it supports max potential 3V-5V) |
| Alarm Output | 2 channels (Dry contact, and it supports max potential 30V) |

Function

| | |
|-----------------|--|
| SD Card | Yes |
| Storage | FTP, Micro SD card (256 G) |
| Max User | 20 (Total bandwidth: 240 M) |
| Browser | IE: IE11, IE10, IE9 Google of high version: 48.0.2564.116 Firefox of high version: 48.0.2 Non-plug edge: 42.17134.1.0 |
| Privacy Masking | 4 areas |

Smart event

| | |
|-------------|---------------------|
| IVS Analyze | Intrusion, tripwire |
| Heat Map | Yes |

Professional, intelligent

| | |
|-----------------|--|
| People Counting | People counting in 4 areas, number of people threshold alarm, 4 queue management, stranding alarm, number of people alarm, number of people heat map, average stranding heat map, track map and export (Report max range is 1 week.) |
|-----------------|--|

Network and port

| | |
|------------------|--|
| Network Protocol | HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP |
| Interoperability | ONVIF (Profile S/Profile G), GB/T28181, CGI |

General

| | |
|-----------------------|--|
| Power Supply | 12V DC /POE |
| Power Consumption | Basic power consumption: 6.2W (12V DC), 9.2W (POE) Max power consumption: (ICR switch, and IR full intensity): 9.2W (12V DC), 12.9W (POE) |
| Operating Temperature | -30°C to +55°C (-22°F to +131°F) |
| Operating Humidity | ≤95% |
| StorageTemperature | -30°C to +70°C (-22°F to +158°F) |
| Storage Humidity | ≤95% |
| Protection Grade | IP67, IK10 |
| Enclosure | Metal + Plastic |

| | |
|---------------|---|
| Dimensions | 59.8 mm × Φ149.8 mm (2.35" × Φ5.9") |
| Net Weight | 0.77 kg(1.70 lb) |
| Gross Weight | 1.16 kg(2.56 lb) |
| Certification | CE-LVD:EN60950-1 EN 55032: 2015, Class B EN 61000-3-2: 2014 EN 61000-3-3: 2013 EN 55024: 2010+A1: 2015 EN 55035: 2017 EN 50130-4: 2011+A1: 2014 CE-EMC:Electromagnetic Compatibility Directive 2014/30/EU FCC:47 CFR FCC Part15, Subpart B, Class B UL/CUL:UL60950-1 CAN/CSA C22.2 No.60950-1-07 |

Ordering Information

| Type | Part Number | Description |
|------------------------|-----------------|-------------------------------------|
| Fisheye | DH-IPC-BW81242P | 12MP AI Fisheye Dome Network Camera |
| | DH-IPC-BW81242N | |
| | IPC-EBW81242P | |
| | IPC-EBW81242N | |
| Accessories (optional) | DH-PFA100 | Adapting plate |
| | DH-PFA132-E | Junction Box |
| | DH-PFB302S | Wall-mount bracket |
| | DH-PFB300C | Celling-mount bracket |

Accessories

Optional:



DH-PFA100
Adapting plate



DH-PFB300C
Celling-mount bracket



DH-PFA132-E
Junction Box



DH-PFB302S
Wall-mount bracket

| Junction Box | Celling Mount | Wall Mount |
|--------------|----------------|----------------|
| PFA132-E | PFB300C+PFA100 | PFB302S+PFA100 |
| | | |

Dimensions (mm/inch)

