

LDV55-SAI400TK

55" Floor-standing Digital Signage



Features:

- High quality panel, industrial-grade design, full metal casing, 3mm tempered protective glass.
- Supports picture, audio, video, PDF, IPC stream, time, weather, etc.
- Dahua MPS platform provides unified remote management for system integrators and media operators.
- Strong 4 core processor provides powerful decoding capabilities, enabling premium display performance.
- Built-in media player software and USB player provide multiple methods to play contents.



Technical Specification

Display

Model	LDV55-SAI400TK
Backlight	LED
Screen Size	55"
Aspect Ratio	9:16
Resolution	2160×3840
Display Colors	1.07B (10 bits)
Brightness	320nits
Contrast Ratio	1000:1
Viewing Angle(H×V)	178°/178°
Display Mode	Portrait
Response Time	8ms
Lifespan	30,000h

Connectivity

Input	RJ45 ×1, USB ×2, TF Slot ×1, HDMI ×1, SIM Slot ×1, 3.5mm Audio In×1
External Control	RS232
Wi-Fi	Not Support
Speaker	5W×2
Smart Signage Platform	Media Publish System 3.0

Touch	Support
-------	---------

Power & Environmental Conditions

Power Supply	AC100-240V, 50/60Hz
Consumption(Typical)	130W
Consumption(Standby)	Less than 0.5W
Operating Temperature	-0°C~+40°C(32°F~104°F)
Operating Humidity	10%~85%

Mechanical Specification

Dimensions	1900mm×752mm×35.2mm(74.8"×29.6"×1.4")
Package	1980mm×915mm×200mm(77.9"×36.0"×7.9")
Net Weight	50kg (110.23lb)
Gross Weight	60kg (132.27lb)

Accessory

Included in Box	Power cord, Pedestal
Optional Mount Kit	NA

Internal Player

Processor	Quad-core Cortex-A17 up to 1.8GHz
Operating System	Android 8.1
RAM	2GB
Storage	16GB
Material Type	Video, audio, image, time, weather, countdown, txt, web page, stream media, pdf
Video	mp4,avi,mov,asf,wmv,mkv A single file can upload up to 2G, and the resolution cannot exceed 4K
Audio	mp3,wma,wav A single file can upload up to 500M
Image	jpg,jpeg,gif,bmp,png A single file can upload up to 30M, and the resolution cannot exceed 4K
Documents	PDF A single file can upload up to 500M
Decoding Capacity	1ch@4K or 4ch@1080P

Dimensions(mm)

